



Bouls Larch steamed 98 mm

Item No. 02-000419



Description

The appearance of this popular furnishing wood is determined by the alternation of light early wood and darker late wood clearly delineated on both sides. This creates tangentially strikingly beautiful veins and radially fine, but also strong stripes, which unfold their decorative effect. The colour of the larch is yellowish brown and pale reddish to strong brick red.

Trade names and other names

German: Lärche gedämpft, Lärche heimisch astrein, Lärche heimisch

English: Steamed Larch, Steamed European Larch

French: Mélèze étuvé, Mélèze d'Europe étuvé

Italian: Larice evaporato, Larice comune evaporato

Spanish: Alerce europeo, Lárice

Dutch: Europese lork, Europese lariks

Portuguese: Alerce, Cedro, Larice-europeu ou Lariço-europeu

Arabic: Lariqs munfad

Chinese: 欧洲杉

Available thicknesses

32, 38, 40, 50, 60, 63, 80, 98 mm, other thicknesses on request.

Occurrence

Widespread over Central Europe with focal points in the Alps, the Carpathians and in Poland, in other parts Larch (*Larix decidua*) is cultivated.

Trunk and bark

The tree of the Larch reaches a height of up to 45m and diameters of up to 1.2m. Larches grown in forests and closed stands are very straight and cylindrical, and up to 2/3 of their length is free of branches. The bark of the larch is smooth and ash-grey on young trees, later becoming up to 3cm thick and barky. Larch has a very high proportion of bark on the trunk and this is 16-24%.




Characteristics and wood colour

The annual rings of Larch are clearly visible due to the broad, dark late wood zones. Larch splint is narrow and light yellowish-brown. The heartwood is dark reddish-brown when fresh, later darkening.

Specifications

Category	Lumber
Product group	Unedged lumber
Thicknesses	98 mm
Weight kg/m3	600.000
Specie	Steamed Larch
Botanical name	Larix decidua
Wood type	Softwood
Main occurrence	Europe
Wood origin	Germany Italy Austria Switzerland Czech Republic
Certification	not certified FSC®100% 100% PEFC
Colour	dark brown
Hue	medium colour
Use	doors construction wood
Surface structure	rough-cut
Humidity	10% ± 2%
Customs tariff number	44071910
Packaging	loosely
Items on stock	yes
Date of delivery	approx. 3 - 6 working days
Postal shipping	nein

Documents

	Prospekt Furniere & Massivholz
	Prospekt Altholz
	Holzdeklaration