

Veneered chipboard panel P2/E1 fumed Oak hell | A/B | mix matched | structure cutterblock wave Item No. 04-001510

Description

We produce high-quality veneered chipboard E1 or CARB P2 in over 120 different veneer wood species. Chipboard, often referred to as flat pressed board (P2 to P7, formerly FYP), consists of different sized glued chips.

Gluing

 $Chipboard\, {\tt E1}, face\, veneer\, gluing\, formal dehyde-free,\, test\, certificate\, {\tt E1}\, in\, the\, composite$

Area of application

Furniture and interior fittings as well as shop fitting and trade fair construction as fronts, fillings, carcasses and back panels

Joining techniques

We distinguish between the following joining techniques how the individual veneer sheets are joined to each other: toppled, planked (also called planked or mixmatch), pushed or twisted pushed.

Standard formats

 $2500\,x\,1250\,\,\text{mm},\,3050\,x\,1250\,\,\text{mm},\,2800\,x\,2070\,\,\text{mm},\,3100\,x\,2070\,\,\text{mm},\,3600\,x\,2070\,\,\text{mm},\,other\,formats\,or\,fixed\,format\,cuts\,on\,request$

Standard thickness incl. veneer

04, 09, 11, 13/14, 16/17, 19/20, 23, 25/26, 29, 39, 51, 61 mm, other thicknesses on request

Backing board versions

veneered chipboard formaldehyde-free, veneered chipboard water-resistant, veneered chipboard flame-retardant

Please enquire about formats, thicknesses and availability in each case.

We supply matching veneers, veneer filler with or without fleece coating on the reverse side and veneer edges for all veneered chipboards. Simply ask us.

Specifications

Category	Panels
Product group	Veneered panels
Lengths	2800 mm
Widths	2070 mm
Thicknesses	20 mm
Tolerance of thickness	±2.0 mm
Weight kg/piece	71.580
Specie	Knotty Oak fumed
Botanical name	Quercus robur/Quercus petraea
Wood type	Hardwood
Wood origin	Central Europe
Manufacturing/origin	Italy Austria Slovakia
Certification	not certified
Substrate	fibreboard
Emission class	E1
Classification	P2
Quality front	A random match (standard quality)
Quality back	B random match (backing quality)
Surface structure	structure cutterblock wave
Surface treatment	untreated
Gluing	PVAC glue D3 according to DIN EN204
Customs tariff number	44129900
Packaging	loosely
Items on stock	on sale (limited stock available)
Date of delivery	approx. 3 - 6 working days
Postal shipping	nein

Documents

사

Prospekt Furnierte Platten