



VILLA RUSTICO 35 by adler | Oak "Smoked G30 Swiss" | rustico | brushed | swiss white oiled

Item No. 07-000732



Description

An oak parquet with a rustic appearance and for lovers of rustic oak floors. Oak is versatile. It can appear calm and elegant, but also lively and wild. And with the right processing technique, a rustic oak parquet can take on a very hearty and unconventional appearance.

Imagine an oak plank with very many knots and cracks, whose rustic character is further emphasised and highlighted by a black putty treatment - that is our VILLA by adler 35 RUSTICO oak plank. A slightly higher proportion of sapwood at the edge of the plank further enhances this effect. The sapwood is the part between the bark and the trunk of the oak tree, it is slightly lighter than the oak wood itself. The lighter sapwood towards the edge of the plank and the bevels on the long side of the plank make this plank flooring something very special.

The three-layer ready-made parquet floor VILLA by adler 35 RUSTICO has a wear layer of oak of approx. 3.5 mm. The parquet floorboards are available in a width of 186 mm and in a length of 1800 to 2000 mm. The surface is machine brushed or textured.

The VILLA by adler 35 RUSTICO plank is formaldehyde-free and complies with fire protection class Cfl-S1. VILLA by adler 35 RUSTICO has the general building authority approval.

Dimensions and packaging

VILLA by adler 35 RUSTICO is available in the dimensions 1800/2000 x 186 x 14 mm and is packed in cartons of 8 planks each.

Assortment

Oak RUSTICO is a very rustic grading according to our factory grading. The knots and cracks are cemented black, which emphasises the rustic character. A share of sapwood is quite possible. In the nature of a more rustic grading, there is the possibility of peeling and wind cracking, which unfortunately cannot be prevented.

Surface treatment & colour variations

The basis of our surface treatment is our NATURA+ WOCA oiled oxidative oil finish on a machine brushed wood structure. This means they go on the "hard" years as the "soft" growth rings have been brushed out. This strengthens the resistance of the surface. We recommend a finish treatment with WOCA maintenance oil after installation for private or commercial use. Wood is a natural product. Depending on the ingredients in the wood and the wood grain, there can always be colour variations in colour-treated surfaces. These colour differences can occur between different product batches, but also within one product batch. This applies in particular to coloured surfaces, as smoking, staining, lyes and the application of colour pigments can lead to different colour shades due to the wood structure. However, this is a testimony to the authenticity of the natural product "wood".

Installation & underfloor heating

The VILLA by adler 35 RUSTICO product can be laid as a floating floor or glued to your screed over the entire surface. We also approve our VILLA by adler 35 RUSTICO plank for hot water-based underfloor heating. The thermal resistance of this product is approx. 0.122 m²k / W (according to EN14342). Should you wish to install this VILLA by adler 35 RUSTICO wood plank on underfloor heating, we always recommend gluing it to your screed over the entire surface. The maximum surface temperature of 23°C to 28°C should not be exceeded. For the exact guidelines for installation on underfloor heating, please refer to the installation instructions.

Care & indoor climate

To ensure that you get a lot of pleasure from your three-layer multilayer parquet after installation, you should care for it accordingly. You should also pay attention to a healthy room climate for your parquet, which is made of the living natural material "wood", but also for you. This exists at a relative humidity of approx. 40 to 60% and a pleasant room temperature of 19 to 22°C. If you do not comply with these guideline values, you should take appropriate care of your parquet. If you do not adhere to these guideline values, your wooden floor can suffer great damage.

Certification










The VILLA plank can be produced as 100% PEFC-certified parquet on request. Please always ask specifically before placing an order whether certified raw material is available.

Specifications

Category	Floors
Product group	Wide plank parquet
Lengths	2000 mm
Widths	186 mm
Thicknesses	14.0 mm
Tolerance of thickness	± 0.4 mm
Weight kg/m2	7.600
Content unit	2.976 m2
Specie	Knotty Oak fumed
Origin	Germany
Wood origin	Central Europe Eastern Europe
Manufacturing/origin	Central Europe Eastern Europe
Colour	white dark brown
Brinell hardness	37 N/mm²

Collection	VILLA RUSTICO by adler
Design	parquet wide plank 1-strip
Construction	3-layer construction
Selection	rustico (very rustic, big knots, black putty)
Wear layer	approx. 3.5 mm
Wood connection	tongue and groove
Surface structure	brushed
Surface treatment	oxidatively oiled
Chamfer	two sided
Laying	full-surface bonding
Floor heating	yes (see additional information)
Thermal resistance (EN 14342)	0.122 m ² k/W (according to EN14342)
Fire rating (EN 13501-1)	Cfl-s1
General Planning Approval	yes
Formaldehyde content (EN 717-1)	E0 < 5 µg/m ³
Emission of PCP (CEN / TR 14823)	unter Nachweisgrenze
Customs tariff number	44187500
Packaging	carton box foiled
Items on stock	yes
Date of delivery	approx. 3 - 6 working days
Postal shipping	nein

Documents

	Produktdatenblatt VILLA 35 RUSTICO by adler (19.01.2023)
	Prospekt Adler Parkett Parkettbuch
	Adler Parkett Verlegeanweisung
	WOCA Pflegeanweisung Parkett
	Adler Parkett Sortimentübersicht
	Adler Parkett Sortierungen
	Adler Fertigparkett Aufheizprotokoll für Fussbodenheizung
	Adler Fertigparkett Leistungserklärung_ EU 305-2011 (30.08.2019)
	Adler Fertigparkett Bauaufsichtliche Zulassung 3-Schichtparkette 2016-2020