



MAXI 35 by adler | Oak "Natur" | classic | brushed | natural-oiled

Item No. 07-000797



Description

Your floor structure only allows a total thickness of 10 mm, but you still don't want to do without a naturally beautiful oak plank floor? Then our two-layer MAXI by adler plank is the right solution for you.

With MAXI by adler, we have a beautiful oak plank with a wear layer of approx. 3.5 mm and a total thickness of just 10 mm in our range. MAXI by adler is available in a width of 186 mm and a length of up to 2200 mm. It is bevelled on the long side, which beautifully underlines the character so typical of country house floorboards. In addition to the natural shade of oak, the colour palette also includes two different shades of white and a somewhat darker, warm smoked oak shade. All planks in the Maxi by adler range are machine-textured and have our naturally warm yet hard-wearing NATURA+ oil finish. On request, we can also supply you with this plank in our premium assortment.

The MAXI by adler plank is formaldehyde-free and approved by the building authorities.

Dimensions and packaging

MAXI by adler is produced in a width of 186 mm and in lengths of 1800 to 2200 mm. The parquet planks are packed in cartons of 10 planks each.

Grading

According to our factory grading, the quality "classic" describes a mixed grading, which can contain both knotty and knotty plank elements. The assortment may have a slight spint content at the edges.

Surface treatment & colour variations

The basis of our surface treatment is our NATURA+ WOCA oiled oxidative oil finish on a machine brushed wood structure, where the "soft years" of the oak are brushed out. We recommend a finish treatment with WOCA maintenance oil after installation for private or commercial use. Wood is a natural product. Depending on the ingredients in the wood and the wood grain, there can always be colour variations in colour-treated surfaces. These colour differences can occur between different product batches, but also within one product batch. This applies in particular to coloured surfaces, as smoking, staining, lye and the application of colour pigments can lead to different colour shades due to the structure of the wood. However, this is a testimony to the authenticity of the natural product "wood".

Installation & underfloor heating

Due to its two-layer structure, this product may only be glued to your screed over the entire surface. Due to its 2-layer construction, this type of parquet is predestined for installation on warm water-based underfloor heating. The thermal resistance of this product is approx. 0.079 to 0.090 m²k / W (according to EN14342). Should you wish to install this MAXI by adler wood plank on an underfloor heating system, we always recommend gluing it to your screed over the entire surface. The maximum surface temperature of 23°C to 28°C should not be exceeded. For the exact guidelines for installation on underfloor heating, please refer to the installation instructions.

Care & indoor climate

To ensure that you get a lot of pleasure from your 2-layer parquet after installation, you should care for it accordingly. You should also pay attention to a healthy room climate for your parquet, which is made of the living natural material "wood", but also for you. This exists at a relative humidity of approx. 40 to 60% and a pleasant room temperature of 19 to 22°C. If you do not comply with these guideline values, you should take appropriate care of your parquet. If you do not adhere to these guideline values, your wooden floor can suffer great damage.

Certification

The MAXI 2-layer plank can be produced as FSC 100% certified parquet on request. Please always ask specifically before placing an order whether certified raw material is available.

Specifications

Category	Floors
Product group	2-layer parquet
Lengths	2200 mm
Widths	186 mm
Thicknesses	10.0 mm
Tolerance of thickness	± 0.4 mm
Weight kg/m2	5.300
Content unit	4.090 m2
Specie	European Oak
Origin	Germany
Wood origin	Central Europe Eastern Europe
Manufacturing/origin	Germany
Colour	light-brown
Brinell hardness	37 N/mm²
Collection	MAXI by adler
Design	parquet short planks 1 strip
Construction	2-layer construction

Selection	classic (mixed selection)
Wear layer	approx. 3.5 mm
Wood connection	tongue and groove
Surface structure	brushed
Surface treatment	oxidatively oiled
Chamfer	two sided
Laying	full-surface bonding
Floor heating	yes (see additional information)
Thermal resistance (EN 14342)	0.079-0.090 m²k/W (according to EN14342)
Fire rating (EN 13501-1)	Dfl-s1
General Planning Approval	yes
Formaldehyde content (EN 717-1)	E0 < 5 µg/m³
Emission of PCP (CEN / TR 14823)	unter Nachweisgrenze
Customs tariff number	44187500
Packaging	carton box foiled
Items on stock	yes
Date of delivery	approx. 3 - 6 working days
Postal shipping	nein

Documents



Produktdatenblatt MAXI 35 by adler (19.01.2023)



Prospekt Adler Parkett | Parkettbuch



Adler Parkett Verlegeanweisung



WOCA Pflegeanweisung Parkett



Adler Parkett | Sortimentübersicht



Adler Parkett | Sortierungen



Adler Fertigparkett Aufheizprotokoll für Fussbodenheizung



Adler Fertigparkett Leistungserklärung_ EU 305-2011 (30.08.2019)



Adler Fertigparkett Bauaufsichtliche Zulassung 2-Schichtparkette 2016-2020