



Veneer Purpleheart 0.56 mm

Item No. 01-000023



Description

A plain texture and a splendid purple to violet colour are the main characteristics of amaranth. The alternating twisted growth makes the fibre course appear irregular, thus growth zones are hardly recognisable. The pores are light, mostly white filled and scattered on a darker ground. The structure of this decorative and unusual wood species is striped, finely needle-cracked and wavy.

Trade names and other names

Abbreviation DIN EN 13556: PGXX
Botanical name: Peltogyne venosa
German: Amarant, Amaranth, Violettholz
English: Purpleheart, Amaranth, Violetwood
French: Amarante, Bois violet, Bois pourpre

Italian: Amarant

Spanish: Amarante, Morado

Portuguese: Pau roxo, Roxinho, Guarabu, Ipe roxo

Dutch: Purperhart

Technical wood properties

Weight fresh/green: 1'100 - 1'300 kg/m³

Density air dry (12-15% u): 800 - 950 kg/m³

Tensile strength: 2.8 - 4.5 N/mm²
Compressive strength: 73 - 85 N/mm²
Flexural strength: 135 - 163 N/mm²
Shear strength: 15 - 17 N/mm²

Hardness according to Brinell BII: 92 N/mm²
Hardness according to Brinell: 49 N/mm²
Differential shrinkage (radial): 0.40 - 0.58%.
Differential shrinkage (tangential): 0.40 - 0.58%

Natural durability (DIN-EN 350-2): 2-3, durable to moderately durable

Values of the technical properties of a wood species refer to a wood moisture content of u 🛮 12% to 15%. Data without guarantee.

Occurrence

Amaranth is native to tropical South and Central America.

Trunk and bark

Amaranth is between 30 and 50m high and has a diameter of 80 to 120 cm.

Characteristics and wood colour

The pores of amaranth are light and scattered on a darker ground, often filled with a white substance. Structure very straight grained and dense. The annual rings are hardly visible in amaranth. The wood of amaranth has a splendid purple to violet colour. Sapwood whitish.

Substitute woods

Bubinga, Tineo, East Indian Rosewood

Literature

- Wood Atlas | 6th edition in 2006 | Rudi Wagenführ
- Wood science volume 1-3 | 1982 | Hans Heinrich Bosshard
- Properties and core sizes of wood species | 1989 | Jürgen Sell / Lignum Switzerland

Specifications

Veneers
Veneers sliced
0.56 mm
0.440
Purpleheart
Peltogyne venosa
Hardwood
South America
Brazil
Germany
not certified
red
medium colour
furniture musical instrument Boat and ship building construction wood
44083900
in bundle, approx. 24-32 sheets
yes
approx. 3 - 6 working days
nein

Documents





Produktblatt Furnier-Imager



Produktblatt mtextur



Holzdeklaration