



Veneered chipboard panel P2/E1 Sycamore | A/B standard | book matched

Item No. 04-000006



Description

We produce high-quality veneered chipboard E1 or CARB P2 in over 120 different veneer wood species. Chipboard, often referred to as flat pressed board (P2 to P7, formerly FYP), consists of different sized glued chips.

Gluing

 $Chipboard\ E1, face\ veneer\ gluing\ formal dehyde-free, test\ certificate\ E1\ in\ the\ composite$

Area of application

Furniture and interior fittings as well as shop fitting and trade fair construction as fronts, fillings, carcasses and back panels

Joining techniques

We distinguish between the following joining techniques how the individual veneer sheets are joined to each other: toppled, planked (also called planked or mixmatch), pushed or twisted pushed.

Standard formats

 $2500\,x\,1250\,mm,3050\,x\,1250\,mm,2800\,x\,2070\,mm,3100\,x\,2070\,mm,3600\,x\,2070\,mm,other formats\,or\,fixed\,format\,cuts\,on\,request$

Standard thickness incl. veneer

04, 09, 11, 13/14, 16/17, 19/20, 23, 25/26, 29, 39, 51, 61 mm, other thicknesses on request

Backing board versions

 $veneered\ chipboard\ formalde hyde-free, veneered\ chipboard\ water-resistant, veneered\ chipboard\ flame-retardant$ $Please\ enquire\ about\ formats, thicknesses\ and\ availability\ in\ each\ case.$

Veneers, fixed veneer mass and veneer edges

We supply matching veneers, veneer filler with or without fleece coating on the reverse side and veneer edges for all veneered chipboards. Simply ask us.

Specifications

Category Panels	
Product group Veneered panels	
Lengths 2800 mm	
Widths 2070 mm	
Thicknesses 26 mm	
Tolerance of thickness ± 0.5 mm	
Weight kg/piece 97.950	
Specie European Sycamo	re
Botanical name Acer pseudoplata	nus
Wood type Hardwood	
Wood origin Switzerland Cent	ral Europe
Manufacturing/origin Italy Austria Slov	vakia
Certification not certified	
Substrate chipboard	
Emission class E1	
Classification P2	
Quality front A book matched (standard quality)
Quality back B (inner side quali	ty)
Surface structure polished	
Surface treatment untreated	
Gluing PVAC glue D3 acco	rding to DIN EN204
Customs tariff number 44129900	
Packaging loosely	
Items on stock on sale (limited st	ock available)
Date of delivery approx. 3 - 6 work	ing days

Documents