



Veneered chipboard panel P2/E1 Birch | A/B | mix matched Item No. 04-000453

# Description

We produce high-quality veneered chipboard E1 or CARB P2 in over 120 different veneer wood species. Chipboard, often referred to as flat pressed board (P2 to P7, formerly FYP), consists of different sized glued chips.

## Gluing

Chipboard E1, face veneer gluing formaldehyde-free, test certificate E1 in the composite

#### Area of application

Furniture and interior fittings as well as shop fitting and trade fair construction as fronts, fillings, carcasses and back panels

#### Joining techniques

We distinguish between the following joining techniques how the individual veneer sheets are joined to each other: toppled, planked (also called planked or mixmatch), pushed or twisted pushed.

## Standard formats

 $2500\,x\,1250\,\text{mm}, 3050\,x\,1250\,\text{mm}, 2800\,x\,2070\,\text{mm}, 3100\,x\,2070\,\text{mm}, 3600\,x\,2070\,\text{mm}, other \,formats\,or\,fixed\,format\,cuts\,on\,request$ 

#### Standard thickness incl. veneer

04, 09, 11, 13/14, 16/17, 19/20, 23, 25/26, 29, 39, 51, 61 mm, other thicknesses on request

## Backing board versions

veneered chipboard formaldehyde-free, veneered chipboard water-resistant, veneered chipboard flame-retardant Please enquire about formats, thicknesses and availability in each case.

Veneers, fixed veneer mass and veneer edges

We supply matching veneers, veneer filler with or without fleece coating on the reverse side and veneer edges for all veneered chipboards. Simply ask us.

# Specifications

ategory	Panels
roduct group	Veneered panels
engths	2800 mm
lidths	2070 mm
hicknesses	19 mm
olerance of thickness	±0.5 mm
leight kg/piece	71.580
pecie	Birch
otanical name	Betulla spp.
lood type	Hardwood
lood origin	Northern Europe
anufacturing/origin	Italy   Austria   Slovakia
ertification	not certified
ubstrate	chipboard
mission class	E1
lassification	P2
uality front	A random match (front quality)
uality back	B random match (backing quality)
urface structure	polished
urface treatment	untreated
luing	PVAC glue D3 according to DIN EN204
ustoms tariff number	44129900
ackaging	loosely
ems on stock	no
ate of delivery	approx. 3 - 4 weeks
ostal shipping	nein

# Documents

