



## Veneered chipboard panel P2/E1 steamed Beech | A/B standard | book matched crowns/half crowns

Item No. 04-001293



---

## Description

We produce high-quality veneered chipboard E1 or CARB P2 in over 120 different veneer wood species. Chipboard, often referred to as flat pressed board (P2 to P7, formerly FYP), consists of different sized glued chips.

### Gluing

Chipboard E1, face veneer gluing formaldehyde-free, test certificate E1 in the composite

### Area of application

Furniture and interior fittings as well as shop fitting and trade fair construction as fronts, fillings, carcasses and back panels

### Joining techniques

We distinguish between the following joining techniques how the individual veneer sheets are joined to each other: toppled, planked (also called planked or mixmatch), pushed or twisted pushed.

### Standard formats

2500 x 1250 mm, 3050 x 1250 mm, 2800 x 2070 mm, 3100 x 2070 mm, 3600 x 2070 mm, other formats or fixed format cuts on request

### Standard thickness incl. veneer

04, 09, 11, 13/14, 16/17, 19/20, 23, 25/26, 29, 39, 51, 61 mm, other thicknesses on request

Backing board versions

veneered chipboard formaldehyde-free, veneered chipboard water-resistant, veneered chipboard flame-retardant  
Please enquire about formats, thicknesses and availability in each case.

Veneers, fixed veneer mass and veneer edges

We supply matching veneers, veneer filler with or without fleece coating on the reverse side and veneer edges for all veneered chipboards. Simply ask us.

Specifications

Category	Panels
Product group	Veneered panels
Lengths	2800 mm
Widths	2070 mm
Thicknesses	16 mm
Tolerance of thickness	± 0.5 mm
Weight kg/piece	60.280
Specie	Beech steamed
Botanical name	Fagus sylvatica
Wood type	Hardwood
Wood origin	Central Europe
Manufacturing/origin	Italy   Austria   Slovakia
Certification	not certified
Substrate	chipboard
Emission class	E1
Classification	P2
Quality front	A book matched (standard quality)
Quality back	B (inner side quality)
Surface structure	polished
Surface treatment	untreated
Gluing	PVAC glue D3 according to DIN EN204
Customs tariff number	44129900
Packaging	loosely
Items on stock	on sale (limited stock available)
Date of delivery	approx. 3 - 6 working days
Postal shipping	nein

Documents

