



## Veneered MDF B2/E1 board panel steamed Beech | A/B standard | book matched

Item No. 04-001307



---

## Description

We produce high-quality noble veneered MDF boards E1 normal flammability with a gross density of approx. 760 kg/m<sup>3</sup> in over 120 different veneer wood species. Medium-density fibreboard or medium-density fibreboard, MDF board for short, is made from finely defibrated, mainly bark-free softwood and by gentle pressing.

### Gluing

Veneer gluing formaldehyde-free with test certificate for the entire product

### Area of application

Furniture and interior fittings as well as shop fitting and trade fair construction as fronts, curved furniture parts, table tops and worktops

### Joining techniques

We distinguish between the following joining techniques how the individual veneer sheets are joined together: topped, planked (also called planked or mixmatch), pushed or twisted pushed.

### Standard formats

2440 x 1220 mm, 3050 x 1220 mm, 2800 x 2070 mm, other formats or fixed format cuts on request

### Standard thickness incl. veneer

04, 06/07, 09/10, 11, 13/14, 16/17, 19/20, 23, 25/26, 29, 31, 39 mm, other thicknesses on request

## Backing board variants

veneered MDF panels flame retardant, veneered MDF panels moisture resistant

Please enquire about formats, thicknesses and availability in each case.

## Veneers, fixed veneer masses and veneer edges

For all veneered MDF panels, we can supply you with matching veneers, veneer filler with or without a fleece coating on the reverse and veneer edges. Simply ask us.

# Specifications

Category	Panels
Product group	Veneered panels
Lengths	2800 mm
Widths	2070 mm
Thicknesses	17 mm
Tolerance of thickness	± 0.5 mm
Weight kg/piece	64.050
Specie	Beech steamed
Botanical name	Fagus sylvatica
Wood type	Hardwood
Wood origin	Central Europe
Manufacturing/origin	Italy   Austria   Slovakia
Certification	not certified
Substrate	fibreboard
Emission class	E1
Classification	P2
Quality front	A book matched (standard quality)
Quality back	B
Surface structure	polished
Surface treatment	untreated
Gluing	PVAC glue D3 according to DIN EN204
Customs tariff number	44129900
Packaging	loosely
Items on stock	on sale (limited stock available)
Date of delivery	approx. 3 - 6 working days
Postal shipping	nein

## Documents

