



Veneered chipboard panel P2/E1 Wenge | A/B | mix matched Item No. 04-001404



Description

We produce high-quality veneered chipboard E1 or CARB P2 in over 120 different veneer wood species. Chipboard, often referred to as flat pressed board (P2 to P7, formerly FYP), consists of different sized glued chips.

Gluing

Chipboard E1, face veneer gluing formaldehyde-free, test certificate E1 in the composite

Area of application

Furniture and interior fittings as well as shop fitting and trade fair construction as fronts, fillings, carcasses and back panels

Joining techniques

We distinguish between the following joining techniques how the individual veneer sheets are joined to each other: toppled, planked (also called planked or mixmatch), pushed or twisted pushed.

Standard formats

 $2500\,x\,1250\,\text{mm}, 3050\,x\,1250\,\text{mm}, 2800\,x\,2070\,\text{mm}, 3100\,x\,2070\,\text{mm}, 3600\,x\,2070\,\text{mm}, other \,formats\,or\,fixed\,format\,cuts\,on\,request$

Standard thickness incl. veneer

04, 09, 11, 13/14, 16/17, 19/20, 23, 25/26, 29, 39, 51, 61 mm, other thicknesses on request

Backing board versions

veneered chipboard formaldehyde-free, veneered chipboard water-resistant, veneered chipboard flame-retardant Please enquire about formats, thicknesses and availability in each case.

Veneers, fixed veneer mass and veneer edges

We supply matching veneers, veneer filler with or without fleece coating on the reverse side and veneer edges for all veneered chipboards. Simply ask us.

Specifications

	Panels
oduct group Ve	/eneered panels
ngths 24	2800 mm
dths 20	2070 mm
icknesses 9) mm
lerance of thickness ±	- 0.5 mm
ight kg/piece 33	33.910
ecie W	Venge
tanical name M	/illetia laurentii
pod type H	fardwood
ood origin A	Africa
nufacturing/origin It	taly Austria Slovakia
rtification n	not certified
bstrate cl	hipboard
ission class E	
assification P	22
ality front A	A random match (front quality)
ality back B	Brandom match (backing quality)
rface structure p	polished
rface treatment u	intreated
Jing P	PVAC glue D3 according to DIN EN204
stoms tariff number 44	14129900
ckaging lc	oosely
ms on stock n	10
te of delivery a	approx. 3 - 4 weeks
stal shipping n	nein

Documents

