

## Edgebanding Larch | 3-layer (approx. 1.50 to 1.80 mm)

Item No. 05-000254



- Variants

UOM:

m1

**100 m**

**please inquire**

CHF 1.19 /m1  
 CHF 0.86 /m1 -30.00%

m1

Stück (je 100 m1)

## Description

The continuous rolls are generally available in **100 or 150 running metres**. We only sell the veneer edgings as entire rolls and cannot unroll smaller quantities. If you want to know the exact quantity m1 per roll, please ask us.

Continuous thick veneer edgings from the roll are produced in multiple layers in thicknesses from 1.0 to 3.0 mm. We stock many types of wood in standard thicknesses of 1.0 mm 2-ply, 1.5 mm 3-ply and 2.0 mm 4-ply as well as standard widths of 24 and 30 mm. The real wood veneer edges are sanded on the surface and thickness-calibrated on the reverse side. The structure of several veneer layers ensures high strength, good milling properties, hardly any distortion and constant dimensional stability. The layers of thick veneer edges are glued with PVAc white glues.

## Finishing options

- fine surface sanding
- thickness calibration on the reverse side
- bonding-friendly backsides
- priming or PVAc pre-coating
- SK pre-coating 180/200/250 g/m2

# Advantages

- highest strength in practically all areas of the edge
- best milling properties
- hardly any warping or twisting
- constant dimensional stability

# Specifications

Category	Panels
Product group	Edgebanding
Widths	24 mm
Thicknesses	1.80 mm
Tolerance of thickness	± 0.05 mm
Weight kg/m <sup>1</sup>	0.026
Specie	Larch
Botanical name	Larix decidua
Wood type	Softwood
Wood origin	Central Europe
Manufacturing/origin	Germany
Certification	not certified
Construction	3-layer
Surface structure	unsanded
Surface treatment	untreated
Gluing	PVAC glue D3 according to DIN EN204
Customs tariff number	44081000
Packaging	on roll
Items on stock	yes
Date of delivery	approx. 2 - 3 working days
Postal shipping	ja