



## Solid parquet Solid 160 | Oak european standard | sanded | natural oiled | 17-000538



## **Specifications**

Product group         Solid parquet           Length         mixed from 430 to 1930 mm, subject to availability           Width         160 mm           Thickness         15-20 mm           Tolerance of thickness         ± 0.5 mm           Weight kg/m2         16.800           Species         EICHEEU           Specie         European Oak           Origin         Austria           Manufacturing/origin         Austria           Colour         light-brown           Brinell hardness         37 N/mm²           Collection         SOLID 125-200           Design         parquet wide plank 1-strip           Construction         1-layer construction           Selection         standard (with small knots)           Wear layer         approx. 4.5-6.0 mm           Wood connection         tongue and groove           Surface structure         polished           Surface treatment         oxidatively oiled	Category	Floors
Width     160 mm       Thickness     15-20 mm       Tolerance of thickness     ± 0.5 mm       Weight kg/m2     16.800       Species     EICHEEU       Specie     European Oak       Origin     Austria       Manufacturing/origin     Austria       Colour     light-brown       Brinell hardness     37 N/mm²       Collection     SOLID 125-200       Design     parquet wide plank 1-strip       Construction     1-layer construction       Selection     standard (with small knots)       Wear layer     approx. 4.5-6.0 mm       Wood connection     tongue and groove       Surface structure     polished	Product group	Solid parquet
Thickness 15-20 mm  Tolerance of thickness ±0.5 mm  Weight kg/m2 16.800  Species EICHEEU  Specie European Oak  Origin Austria  Manufacturing/origin Austria  Colour light-brown  Brinell hardness 37 N/mm²  Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Length	mixed from 430 to 1930 mm, subject to availability
Tolerance of thickness ± 0.5 mm  Weight kg/m2 16.800  Species ELCHEEU  Specie European Oak  Origin Austria  Manufacturing/origin Austria  Colour Ilight-brown  Brinell hardness 37 N/mm²  Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Width	160 mm
Weight kg/m2     16.800       Species     EICHEEU       Specie     European Oak       Origin     Austria       Manufacturing/origin     Austria       Colour     light-brown       Brinell hardness     37 N/mm²       Collection     SOLID 125-200       Design     parquet wide plank 1-strip       Construction     1-layer construction       Selection     standard (with small knots)       Wear layer     approx. 4.5-6.0 mm       Wood connection     tongue and groove       Surface structure     polished	Thickness	15-20 mm
Specie European Oak Origin Austria Manufacturing/origin Austria Colour light-brown Brinell hardness 37 N/mm² Collection SOLID 125-200 Design parquet wide plank 1-strip Construction 1-layer construction Selection standard (with small knots) Wear layer approx. 4.5-6.0 mm Wood connection tongue and groove Surface structure polished	Tolerance of thickness	±0.5 mm
Specie European Oak Origin Austria Manufacturing/origin Austria Colour light-brown Brinell hardness 37 N/mm² Collection SOLID 125-200 Design parquet wide plank 1-strip Construction 1-layer construction Selection standard (with small knots) Wear layer approx. 4.5-6.0 mm Wood connection tongue and groove Surface structure polished	Weight kg/m2	16.800
Origin Austria  Manufacturing/origin Austria  Colour light-brown  Brinell hardness 37 N/mm²  Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Species	EICHEEU
Manufacturing/origin Austria  Colour light-brown  Brinell hardness 37 N/mm²  Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Specie	European Oak
Colour light-brown  Brinell hardness 37 N/mm²  Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Origin	Austria
Brinell hardness 37 N/mm²  Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Manufacturing/origin	Austria
Collection SOLID 125-200  Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Colour	light-brown
Design parquet wide plank 1-strip  Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Brinell hardness	37 N/mm <sup>2</sup>
Construction 1-layer construction  Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Collection	SOLID 125-200
Selection standard (with small knots)  Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Design	parquet wide plank 1-strip
Wear layer approx. 4.5-6.0 mm  Wood connection tongue and groove  Surface structure polished	Construction	1-layer construction
Wood connection tongue and groove Surface structure polished	Selection	standard (with small knots)
Surface structure polished	Wearlayer	approx. 4.5-6.0 mm
	Wood connection	tongue and groove
Surface treatment oxidatively oiled	Surface structure	polished
	Surface treatment	oxidatively oiled

Chamfer	four sided
Laying	full-surface bonding
Floorheating	yes (see additional information)
Customs tariff number	44187500
Packaging	loosely packed
Items on stock	no
Date of delivery	approx. 3 - 6 weeks
Postal shipping	nein