



3-layer wall panel reclaimed Sp/Fi/Pi type 1F polished

Item No. 08-000009



Description

The wall panelling with a three-layer construction of reclaimed wood is bevelled and offers the possibility of mounting individual planks on the wall as well as on the ceiling. The 3-layer reclaimed wood planks are tongue and groove all around. The top lamellas in reclaimed spruce/fir/pine type 1F are cut from old beams or old floor boards (2nd patina), steamed and sanded. They have an intensive worm pattern with cracks.

Available width

Plank widths between 150 and 330 mm, also available in special or fixed widths at an extra charge.

Available lengths

falling from 1800 to 5000 mm, also available in fixed lengths at an extra charge

Structure

Thickness 19 mm = 6.5/6.5/6.5 mm, other thicknesses on request

Middle layer

The middle layer of the 3-layer wall cladding made of reclaimed wood consists of "new spruce".

Rear side/counter-pull

The back is made of spruce/fir new as standard, sanded and not patched.

Range of application

The wall panelling offers a variety of possible uses for walls and ceilings.

Optics: patching

Cracks or knotholes are repaired by hand with real wood or partially patched with old wood putty. The result is a visually harmonious and natural old wood surface. We do not use silicone or similar chemical fillers for patching, as these only disturb the look and feel of a surface. Chemically repaired areas attract dust and are difficult to clean.

Optics: grading

Only trained and motivated personnel with sufficient experience create old wood surfaces with a unique character. A harmonious appearance and consistent quality for each plank is particularly important. Precise guidelines and a great deal of intuition for a well-balanced grading prevent murals with a "zebra look", which disturb the overall picture and make it appear unsettled.

Optics: Pests

Only an infestation of the knock beetle beautifies the old wood and gives the surface a unique look. We do not use any raw wood for our three-layer wall panels that has been destroyed by the house longhorn beetle or by white, brown and blue rot.

Specifications

Category	Reclaimed Wood Wall and Ceiling
Product group	3-layer wall panels
Length	mixed from 2000 to 5000 mm, subject to availability
Width	mixed from 8 up to 22 cm, main widths from 12 to 18 cm
Thicknesses	19 mm
Weight kg/m ²	9.200
Specie	Reclaimed Spruce steamed
Botanical name	Picea abies/Abies alba/Pinus sylvestris
Wood type	Softwood
Wood origin	Central Europe
Manufacturing/origin	Austria Slovakia
Certification	not certified CE label
Colour	brown
Hue	medium colour
Profile	floor board
Construction	3-layer construction
Quality front	reclaimed wood 2nd patina
Wood connection	tongue and groove
Surface structure	polished

Surface treatment	untreated
Humidity	10% ± 2%
Customs tariff number	44219900
Packaging	loosely
Items on stock	no
Date of delivery	approx. 3 - 6 weeks
Postal shipping	nein

Documents



Prospekt Altholz
