



## 3-layer wall panel reclaimed Sp/Fi/Pi type 1G brushed

Item No. 08-000010



---

## Description

The wall panelling with a three-layer construction of reclaimed wood is bevelled and offers the possibility of mounting individual planks on the wall as well as on the ceiling. The 3-layer reclaimed wood planks are tongue and groove all around. The top lamellas in reclaimed spruce/fir/pine type 1G are cut from old beams or old floor boards (2nd patina), steamed and brushed. They have an intensive worm pattern with cracks.

## Available width

Plank width between 150 and 330 mm, also available in special or fixed widths at an extra charge.

## Available lengths

falling from 1800 to 5000 mm, also available in fixed lengths at an extra charge

## Structure

Thickness 19 mm = 6.5/6.5/6.5 mm, other thicknesses on request

## Middle layer

The middle layer of the 3-layer wall cladding made of reclaimed wood consists of "new spruce".

## Rear side/counter-pull

The back is made of spruce/fir new as standard, sanded and not patched.

## Range of application

The wall panelling offers a variety of possible uses for walls and ceilings.

## Optics: patching

Cracks or knotholes are repaired by hand with real wood or partially patched with old wood putty. The result is a visually harmonious and natural old wood surface. We do not use silicone or similar chemical fillers for patching, as these only disturb the look and feel of a surface. Chemically repaired areas attract dust and are difficult to clean.

## Optics: grading

Only trained and motivated personnel with sufficient experience create old wood surfaces with a unique character. A harmonious appearance and consistent quality for each plank is particularly important. Precise guidelines and a great deal of intuition for a well-balanced grading prevent murals with a "zebra look", which disturb the overall picture and make it appear unsettled.

## Optics: Pests

Only an infestation of the knock beetle beautifies the old wood and gives the surface a unique look. We do not use any raw wood for our three-layer wall panels that has been destroyed by the house longhorn beetle or by white, brown and blue rot.

## Specifications

Category	Reclaimed Wood   Wall and Ceiling
Product group	3-layer wall panels
Length	mixed from 2000 to 5000 mm, subject to availability
Width	mixed from 8 up to 22 cm, main widths from 12 to 18 cm
Thicknesses	19 mm
Weight kg/m <sup>2</sup>	9.200
Specie	Reclaimed Spruce steamed
Botanical name	Picea abies/Abies alba/Pinus sylvestris
Wood type	Softwood
Wood origin	Central Europe
Manufacturing/origin	Austria   Slovakia
Certification	not certified   CE label
Colour	brown
Hue	medium colour
Profile	floor board
Construction	3-layer construction
Quality front	reclaimed wood 2nd patina
Wood connection	tongue and groove
Surface structure	brushed

---

Surface treatment	untreated
Humidity	10% ± 2%
Customs tariff number	44219900
Packaging	loosely
Items on stock	no
Date of delivery	approx. 3 - 6 weeks
Postal shipping	nein

---

## Documents



Prospekt Altholz

---